



单位: mm
*为检验尺寸

Technical Requirements

Trademark panel+ammeter+4/10 partition+1 position indicator+2 position IP air switch (type II plastic case)+(trademark panel+2-bit IEC C19+trademark panel+10-bit IEC C13) * 2+4/10 partition

Input voltage range: Between 220 - 250V AC
 Input frequency: 50 Hz
 Maximum input current each phase: 32A
 Power cable: Use a flexible cable with a cross section of 3x6 mm²
 Input Plug: Male Plug, IEC60309, 32A 2P + E, IP 44
 Standard output connection: 20 * IEC 320 C13
 4 * IEC 320 C19

Overcurrent protection: Built-in 2 protection CBs (16A each)
 Operating humidity: Minimum in the range of 5% ~ 95% dew-free or wider
 Power cord locking mechanism: There is a locking mechanism for the power cord and PDU

产品名称: Product Name	Power Distribution Unit
客户型号: Customer No.	-
公司型号: Model No.	PDU08-11-CF2004-S1X1Y2
图样编号: Drawing No.	20230308-03
公差: Tolerance: ±2	比例: Scale: 1:1

1 2 3 4 5 6

A B C D E F

1481.9
1460.25
1406.9

M3*6 ground screw

47

56

9.2

42

42

2*IEC C19

10*IEC C13

10*IEC C13

2*IP circuit breaker (16A)

2*IEC C19

10*IEC C13

10*IEC C13

4 5 6